

Dry Block TEMPERATURE CALIBRATOR

T Series

APPLICATION: IDEAL FOR CALIBRATION OF THERMOCOUPLES, RTD, GAUGES, THERMOMETERS, SWITCHES, TRANSMITTERS ETC.

Features

- * Dry Block
- * Fast Heating & Cooling
- * Controlled through PID Controller
- * Good Stability
- * Power Supply for Transmitters
- * Facility to check Temperature Switch Test

BLOCK DIMENSION

Block Diameter 25.4mm
Block Depth 120mm
Insertion Tube Depth 110mm

Specifications for Dry Block Temperature Calibrator

Model 100 T
Range 35 to 100 °C
Accuracy ±0.5 °C
Stability ±0.2 °C
Resolution 0.1 °C
Units °C / °F Switchable
Switch Test 5V DC Nominal
Power Supply 230V AC ± 5%/50Hz
Transmitter Supply 12 to 24V DC

Standard Delivery

- | | |
|----------------------------|---------------------------------------------------|
| 1. Instrument | : 1 No |
| 2. Power Cable | : 1 No |
| 3. Carrying Case | : 1 No |
| 4. Test Leads | : 1 No |
| 5. Insertion Tube | : ¼", ½" |
| 6. Insertion Tool | : 1 No |
| 7. User Manual | : 1 No |
| 8. Calibration Certificate | : Traceable to National / International Standards |



R&D Instrument Services

(Specialist in Calibration & Instruments)

5/3A, Poomagal 3rd Street, Ambal Nagar,
Ekkattuthangal, Chennai 600032.
Tamilnadu, India. Telefax: +91-44-2225 0126.
Cell: 93827 44155, 93810 38463.
email: sales@rndinstruments.com
www.rndinstruments.com